

# Toebehoren

## Aanbevolen drivers

	Led-driver 250mA, 10W	Led-driver 250mA, 10W, PHASE	Led-driver 250 mA, 20W, DALI	Led-driver 700mA, 30W	Led-driver 500mA, 30W, PHASE	Led-driver 500mA, 40W, DALI
	<b>S</b>	<b>S</b>	<b>S</b>	<b>M</b>	<b>M</b>	<b>M</b>
	250mA	250mA	250/350/500/700mA	500/600/700mA	500mA	250/350/500/700mA
<b>Materiaal</b>	Polycarbonaat (PC)	Polycarbonaat (PC)	Polycarbonaat (PC)	Polycarbonaat (PC)	Polycarbonaat (PC)	Polycarbonaat (PC)
<b>Kleur</b>	wit	wit	wit	wit	wit	wit
<b>Spanning prim.</b>	220-240V ~ 50/60Hz	220-240V ~ 50/60Hz	220-240V ~ 50/60Hz	220-240V ~ 50/60Hz	220-240V ~ 50/60Hz	220-240V ~ 50/60Hz
<b>Spanning sec.</b>	26-40V	30-42V	6-60V	30-42V	42-60V	6-58V
<b>Uitgangsstroom</b>	250mA	250mA	250/350/500/700mA	500/600/700mA	500mA	250/350/500/700mA
<b>Aantal uitgangen sec.</b>	1	1	1	1	1	1
<b>Vermogen van</b>	6,5W	7,5W	1,5W	15W	21W	1,5W
<b>Vermogen tot</b>	10W	10W	15W	29,5W	30W	40,6W
<b>Omgevingstemp. min.</b>	-20°C	-20°C	-20°C	-20°C	-25°C	-25°C
<b>Omgevingstemp. max.</b>	45°C	50°C	50°C	50°C	50°C	50°C
<b>Temperatuur-beveiliging</b>	110°C	110°C	110°C	110°C	110°C	110°C
<b>IP-beschermings-klasse</b>	IP 20	IP 20	IP 20	IP 20	IP 20	IP 20
<b>Dimbaar</b>	-	PHASE C	DALI	-	PHASE C	DALI
<b>Lengte</b>	6,5 cm	8,5 cm	15 cm	14,7 cm	13,8 cm	12,3 cm
<b>Breedte</b>	3,9 cm	3,9 cm	5,2 cm	4,3 cm	4,4 cm	7,9 cm
<b>Hoogte</b>	2 cm	2,2 cm	2,8 cm	3 cm	3 cm	2,4 cm
<b>Gewicht</b>	0,05 kg	0,05 kg	0,142 kg	0,105 kg	0,13 kg	0,21 kg
<b>Art. nr.</b>	1004058	1004055	1004067	1004064	1004054	1004069
<b>EUR</b>	23,00	36,00	72,00	27,00	52,00	72,00

	<b>S</b>				<b>M</b>			
<b>Uitvoering</b>	SL153 elliptisch	SL154 prismatisch	SL155 mat	SL305 honingraat	SL153A elliptisch	SL154A prismatisch	SL155A mat	SL306 honingraat
<b>Art. nr.</b>	1004786	1004787	1004788	1004789	1004790	1004791	1004792	1004793
<b>EUR</b>	3,50	4,00	4,00	6,50	3,50	4,50	4,50	9,75