


LED DRIVER

250-700mA | 20W incl. trekontlasting



Productinformatie

220-240V ~50/60Hz
Materiaal: PC
l: 15 cm b: 5,2 cm h: 2,8 cm
Dimbaar: 1-10V / Dali

Opmerking

250/350/500/700mA
Uitgangsstroom via DIP-switch instelbaar


Spanning sec.	6-60V
Vermogen van	1,5W
Vermogen tot	20W
Temperatuurbeveiliging	110°C
Vermogensfactor	0,9

Variant	Art. nr.	EUR
<input type="checkbox"/> wit	1002423	75,00

Fabrikant: WeiSen Electronic Co., Ltd

LED DRIVER

250-700mA | 40W incl. trekontlasting



Productinformatie

220-240V ~50/60Hz
Materiaal: PC
l: 12,3 cm b: 7,9 cm h: 2,4 cm
Dimbaar: 1-10V / Dali

Opmerking

250/350/500/700mA
Uitgangsstroom via DIP-switch instelbaar


Spanning sec.	6-58V
Vermogen van	1,5W
Vermogen tot	40W
Temperatuurbeveiliging	110°C
Vermogensfactor	0,9

Variant	Art. nr.	EUR
<input type="checkbox"/> wit	1002424	80,00

Fabrikant: WeiSen Electronic Co., Ltd

LED DRIVER DALI

350-1050mA | 60W incl. trekontlasting



Productinformatie

220-240V ~50/60Hz
Materiaal: PC
l: 12,4 cm b: 7,9 cm h: 2,2 cm
Dimbaar: 1-10V / Dali

Opmerking

350/500/550/650/700/750/
850/900/1000/1050mA
Uitgangsstroom via DIP-switch instelbaar


Spanning sec.	2-74V
Vermogen van	1W
Vermogen tot	60W
Temperatuurbeveiliging	110°C
Vermogensfactor	0,95

Variant	Art. nr.	EUR
<input type="checkbox"/> wit	464032	130,00

Fabrikant: TCI Telecomunicazioni Italia Srl

LED DRIVER DALI

700-1500mA | 50W incl. trekontlasting



Productinformatie

220-240V ~50/60Hz
Materiaal: PC
l: 12,3 cm b: 7,9 cm h: 2,4 cm
Dimbaar: 1-10V / Dali

Opmerking

700/800/900/1050/1200/1300/1400mA
Uitgangsstroom via DIP-switch instelbaar

Spanning sec.	6-58V
Vermogen van	4,2W
Vermogen tot	50W
Temperatuurbeveiliging	110°C
Vermogensfactor	0,9

Variant	Art. nr.	EUR
<input type="checkbox"/> wit	1002425	85,00

Fabrikant: WeiSen Electronic Co., Ltd

