




KALU
CW, PHASE

220 - 240 V ~ 50/60 Hz | 350 mA
Materiaal: aluminium / polycarbonaat (PC)

KALU
CW, single, PHASE


		A → G
1000127, 1000128	1000lm 3000K	A t G E

Variant	Art. nr.
1000 lm 3000 K 60° CRI 80	
■ zwart	1000127
1000 lm 3000 K 60° CRI 80	
■ wit / zwart	1000128

KALU
CW, double, PHASE


		A → G
1000129, 1000130	2000lm 3000K	A t G E

Variant	Art. nr.
2000 lm 3000 K 60° CRI 80	
■ zwart	1000129
2000 lm 3000 K 60° CRI 80	
■ wit / zwart	1000130

KALU
CW, triple, PHASE

		A → G
1000131, 1000132	3000lm 3000K	A t G E

Variant	Art. nr.
3000 lm 3000 K 60° CRI 80	
■ zwart	1000131
3000 lm 3000 K 60° CRI 80	
■ wit / zwart	1000132

KALU
CW, quad, PHASE

		A → G
1000135, 1000136	4000lm 3000K	A t G E

Variant	Art. nr.
4000 lm 3000 K 60° CRI 80	
■ zwart	1000135
4000 lm 3000 K 60° CRI 80	
■ wit / zwart	1000136