



GALEN 60 SP





IP 65 IK03 L70B50 180° 11 12

220-240 V ~ 50/60 Hz | 450 mA
Systeemvermogen: 18 W
Materiaal: aluminium/glas

		A → G
1003447	1570/1570lm 3000/4000K	A+ G E

Variant	Art. nr.
1570/1570 lm 3000/4000 K CRI 80	
■ antraciet	1003447

GALEN 120 SP





IP 65 IK03 L70B50 180° 11 10

220-240 V ~ 50/60 Hz | 900 mA
Systeemvermogen: 34 W
Materiaal: aluminium/glas

		A → G
1003448	3000/3100lm 3000/4000K	A+ G E

Variant	Art. nr.
3000/3100 lm 3000/4000 K CRI 80	
■ antraciet	1003448

FLAC BEAM® SP



IP 65 IK04 60° L70B50 120° 170°

200

220-240 V ~ 50/60 Hz
Systeemvermogen: 27 W
Materiaal: aluminium

- IP44 geaarde stekker

Informatie over de energie-efficiëntieklasse voor dit product waren bij de druk nog niet beschikbaar. De nieuwste productgegevens vindt u te allen tijde op www.slv.com

Variant	Art. nr.
1800 lm 3000 K CRI 90	
■ grijs	231072