








RUSTY® PATHLIGHT 40 Pole



RUSTY® PATHLIGHT 70 Pole



RUSTY® PATHLIGHT Pole, TCR-TSE



220-240 V ~ 50/60 Hz  
 Systemvermogen: 8,9 W  
 Materiaal: FeCSI-staal / polycarbonaat (PC)

220-240 V ~ 50/60 Hz  
 Systemvermogen: 8,9 W  
 Materiaal: FeCSI-staal / polycarbonaat (PC)

220-240 V ~ 50/60 Hz  
 Materiaal: FeCSI-staal / polycarbonaat (PC)

- Open kabeleinde

- Open kabeleinde

- Open kabeleinde

1001823	400lm 3000K	

1001824	400lm 3000K	

GX53 < 9 W  
 Ø: 7,5 cm L: 2,7 cm

LED GX53 | 6 W | 120°  
 4000 K | 550 lm | EEK=F  
 6 kWh / 1000 h

Art. nr. 1005269

■ IP68 verbindingsbox, 3-polig  
 Art. nr. 228730  
 ■ Grondpin  
 Art. nr. 229422

■ IP68 verbindingsbox, 3-polig  
 Art. nr. 228730  
 ■ Grondpin  
 Art. nr. 229422

■ IP68 verbindingsbox, 3-polig  
 Art. nr. 228730  
 ■ Grondpin  
 Art. nr. 229422

Variant	Art. nr.
400 lm   3000 K   CRI 80	
■ roest	1001823

Variant	Art. nr.
400 lm   3000 K   CRI 80	
■ roest	1001824

Variant	Art. nr.
1xGX53	
■ roest	230090